



SUPERLIFT
SANITARY LIFTS

PALLET TRUCKS

Stainless Steel Uplift Pallet Trucks

Capacity 3,000 lbs to 16,000 lbs

The Superlift Stainless Steel Uplift Pallet Truck are manufactured entirely of stainless steel and specially designed for corrosive environments and other applications that demand high standards of hygiene, such as food processing and pharmaceutical industries.



- Pharma grade 304L or 316L electro polished
- Fully Welded
- No cracks or crevices



- 3,000 lbs capacity
- 304 L
- 27" x 48" forks
- Lithium battery
- Small profile for clean room and RTE food application



- 4,500 lbs capacity
- 304 Stainless steel
- Exceptional value

Options

- 316L Stainless steel
- Rider platforms
- Capacities to 10,000 lbs



Stainless Steel Uplift Pallet Trucks

Capacity 3,000 lbs specifications

General data	
Manufacturer's type designation	PTE15N
Drive	Battery
Operator type	Pedestrian
Load capacity/rated load	1.5 T
Load centre distance	23.6"
Load distance centre or drive axle to fork	37.2"
Wheelbase	46.5"

Weight		
Service weight	271lbs	277lbs
Axle loading, laden front/rear	1,102lbs/2,475lbs	1,380lbs/2,204lbs
Axle loading, unladen front/rear	211lbs/59.5lbs	218lbs/59lbs

Tires, chassis	
Tires	Polyurethane (PU)
Tires size front	8.2" x 2.7"
Tires size rear	3.1"x 3.6" (optional tandem 3.1" x 2.7")
Additional wheels (dimensions)	-/3.1"x 1.2"
Wheel number front/rear	1x / 2 (1x/4) or 1x +2/2 (1x+ 2/4)
Tread front	-/420
Tread rear	15" 20.6"

Dimensions	
Lift	4.5"
Height of tiller in drive position min./max.	27.5"/6.2"
Height, lowered	3.14"
Overall length	60.2"
Length to face of forks	12"
Overall width	21.1" 27"
Fork dimensions	1.8"/6.2"/45.2"
Distance between fork-arms	21.1" 27"
Ground clearance, centre of wheelbase	1.2"
Aisle width for pallets lengthways safe distance	78.7"
Turning radius	52.3"



SUPERLIFT
SANITARY LIFTS

Stainless Steel Uplift Pallet Trucks

Capacity 3,000 lbs specifications (continued)

Performance data

Travel speed, laden/unladen	4.6/4.8 km/h
Lift speed, laden/unladen	0.020/0.025 m/s
Lowering speed, laden/unladen	0.05/0.04 m/s
Max. gradeability, laden/unladen	4/16%
Service brake	Electromagnetic

Electric-specifications

Drive motor rating S2 60 min	0.65 kW
Lift motor rating at S3 10%	0.50 kW
Battery acc to DIN 43531/35/36A, B, C, no	No
Battery voltage, nominal capacity K5	24V/20 (optional: 24V/30, 24V/36)
Battery weight	10lbs
Energy consumption acc to VDI cycle	0.18 kWh/h

Addition Data

Type of drive control	DC speed control
Sound level at driver's ear acc to EN12053	<70 dB(A)

